

HANDLINE NOZZLES

CHIEF™

BASE SIZE	PSI (BAR)	AVAILABLE STANDARD FLOW RATE GPM (LPM)														BASE TYPE			SHUT-OFF	HANDLE	TEETH			MODEL					
		15 (57)	30 (114)	45 (170)	60 (227)	75 (284)	95 (360)	125 (473)	150 (568)	175 (662)	185 (700)	200 (757)	250 (946)	275 (1041)	300 (1136)	325 (1230)	350 (1325)	Rigid			Swivel	Free Swivel	Twist		Ball	Tab	Horseshoe	Spinning Plastic	Molded Urethane
		1"	150 (6.89)	•	•	•	•													s							s		
1.5"	50 (3.45)																	o	s							s	o	4000-14	
	75 (5.17)																												4000-19
	100 (6.89)				•		•	•	•																				4000-22
	50 (3.45)									160	•							s										s	4000-14HR
	75 (5.17)																												4000-19
	100 (6.89)				•	•	•	•	•										o	s		•				s	o		4000-22
	50 (3.45)																		o	s		•				s	o		4000-22
	75 (5.17)																		o	s						s	o		4000-24
	100 (6.89)																		o	s						s	o		4000-24
2.5"	50 (3.45)																		s		•				s	o		4000-22	
	75 (5.17)																		s						s	o		4000-22	
	100 (6.89)																		s						s	o		4000-24	
	50 (3.45)																		s						s	o		4000-24	



Chief Tips

BASE SIZE	PSI (BAR)	AVAILABLE STANDARD FLOW RATE GPM (LPM)														BASE TYPE			SHUT-OFF	HANDLE	TEETH			MODEL							
		15 (57)	30 (114)	45 (170)	60 (227)	75 (284)	95 (360)	125 (473)	150 (568)	175 (662)	185 (700)	200 (757)	250 (946)	275 (1041)	300 (1136)	325 (1230)	350 (1325)	Rigid			Swivel	Free Swivel	Twist		Ball	Tab	Horseshoe	Spinning Plastic	Molded Urethane	Cut Metal	
		1"	100 (6.89)	•	•	•	•														s		•	s	o	s				4000-02	
1.5"	50 (3.45)																		s				•	o	s	s	o		4000-10		
	75 (5.17)																							•	o	s	s	o		4000-12	
	100 (6.89)				•	•	•	•	•																•	o	s	s	o		4000-16
	50 (3.45)																								•	o	s	s	o		4000-20
	75 (5.17)																			s	o				•	o	s	s	o		4000-10
	100 (6.89)																			s	o				•	o	s	s	o		4000-12
	50 (3.45)																			s	o				•	o	s	s	o		4000-20
	75 (5.17)																			s	o				•	o	s	s	o		4000-12
	100 (6.89)																			s	o				•	o	s	s	o		4000-26
2.5"	50 (3.45)																		s	o				•	o	s	s	o		4000-10	
	75 (5.17)																		s	o				•	o	s	s	o		4000-12	
	100 (6.89)																		s	o				•	o	s	s	o		4000-26	



Chief Nozzles

Key: s = Standard o = Option
 X = Flow rates available on the Chief XD
 • = Flow rates not available on the Chief XD

HANDLINE NOZZLES

1-12