

MMED6000RD-FG6

Handheld Multi-Parameter Patient Monitor

The portable multi-parameter monitor is intended for checking the TEMP, ECG, NIBP, SpO_2 and PR of adult in medical unit (including remote medical center, patient room and ward). This equipment is not for ICU use.

C € 0123

FEATURES

- Colorful TFT display
- Smart design, easy to use, portable size
- Real time monitoring NIBP, SpO2, ECG, pulse rate, temperature
- powerful compatibility and easy to install
- Humanization design: choose NIBP setting from manual or automatic check

TECHNICAL SPECIFICATIONS

| Application Range | | | | |
|--------------------------|---|-----------------------|---|--|
| adult | | | | |
| SpO ₂ | | Pulse Rate | | |
| Measurement range: | 70%~100% | Measurement range: | 30bpm~250bpm | |
| Resolution: | 1% | Resolution: | 1bpm | |
| Measurement accuracy: | 70%~100% ±2%; 0%~69% no definition | Measurement accuracy: | ±2bpm or ±2% the larger one | |
| ECG | | Heart Rate | | |
| Standard lead: | I, II, V | Heart rate range: | 15bpm \sim 300bpm | |
| Sampling rate: | 250Hz/s | Accuracy: | 15bpm \sim 99bpm,±1bpm; 100bpm \sim 300bpm, ±2%. | |
| CMRR: | 89dB | Resolution: | 1bpm | |
| NIBP | | TEMP | | |
| Measuring range: | 0mmHg~270mmHg | Measuring range: | $25^{\circ}\text{C} \sim 45^{\circ}\text{C}$; | |
| Resolution: | 1mmHg | Resolution: | ±0.1°C; | |
| Measurement accuracy: | ±3mmHg | Measurement accuracy: | ≤±0.2℃ | |
| Display | | Dimensions and weight | | |
| Туре: | TFT 3.5inch; 76mm×54mm; | Dimension: | 167mm ×103mm × 48mm | |
| Parameters: | ECG waveform, HR, %SpO2, Temperature, BP (systolic, diastolic and mean) | Weight: | ≤600g (including batteries) | |
| Power Requirements | | | | |
| Battery: | DC 7.4V,one rechargeable lithium battery; | power adapter: | MENB1030A0900F02; Output: 9V DC, 3A | |
| | · | • | | |

Environment Requirements

| Operation Temperature: | 5℃~40℃ | Operation Humidity: | ≤80% no condensation | | | |
|----------------------------|-------------------------|-------------------------|-----------------------|-------------|--|--|
| Storage Temperature: | -20°C~+55°C | Storage Humidity: | ≤93%, no condensation | | | |
| Accessories | | | | | | |
| One SpO ₂ probe | One NIBP cuff for adult | One Temperature prob | One ECG cable | One charger | | |
| One Power adapter | One Rechargeable | a pack of ECG electrode | One Hang | One User | | |
| and power cord | Lithium battery | for single use | bag | manual | | |
| One Quick operation guide | | | | | | |

Beijing Choice Electronic Tech Co., Ltd.

Room 4104, No. A12 Yuquan Road, Haidian District, Beijing 100143, P.R.China Website: www.choicemmed.com Email: market@choicemmed.com

ChoiceMMed Providing a Better Life

NOTE The specifications are subject to changes without prior notice. Revised Date: Jan 30, 2019