



FLOW GAUGES & HOSE/NOZZLE ACCESSORIES

LINE GAUGE - 228A

- Fully guarded, shock resistant luminescent gauge
- Hard anodized cast Elk-O-Lite® body
- 228A – 1.5" 0-200 gauge with 1.5" free swivel inlet, 1.5" outlet, and 6" length
- 228A – 2.5" 0-200 gauge with 2.5" free swivel inlet, 2.5" outlet, color-coded zones, and 6.9" length



PIEZOMETER GAUGE - 227A

- Liquid-filled 0-300 psi gauge
- Elk-O-Lite® construction with hard anodized finish
- 227A – 1.5" (1.5" swivel inlet, 1.5" outlet, and 4.8" length)
- 227A – 2.5" (2.5" swivel inlet, 2.5" outlet, and 5.5" length)



PISTOL GRIP ADAPTER - PG

- For use with 1.5", 1.75" or 2" handline nozzles
- Elk-O-Lite® construction with hard anodized finish
- PG-S (1" free swivel inlet and waterway with 1" male outlet)
- PG (1.5" free swivel inlet and waterway with 1.5" female outlet)



DIRECT CONNECT ADAPTER - D-327

- 2.5" inlet
- 1.5" outlet
- Rigid base
- D-327 (Brass construction)
- D-327A (Elk-O-Lite® construction)



STANDPIPE FLOWMETER - 555A

- Compact design for high-rise kit applications
- Elk-O-Lite® construction with hard anodized finish
- Dual LED display - pressure and flow
- 45° swivel elbow
- 2.5" female swivel inlet / 2.5" threaded male discharge
- 250 GPM (946 LPM) maximum flow
- 250 PSI (17.2 BAR) max operating pressure
- Weight: 5 lb. 4oz. (2.38 kg)

