

65-Gallon Wheeled Poly-Overpack Salvage Drum

SYK650



Acquired CE Certification, comply with the regulations of EPA 40 CFR 264.175 of EPA and SPCC as well as U.S. NPDES.

65-Gallon Wheeled Poly-Overpack Salvage Drum(Universal)

SYSBEL 65-Gallon Wheeled Poly-Overpack Salvage Drums are special containers which are suitable for temporary storage and transport of hazardous waste. Widely used in secondary packaging, transportation, emergency spill treatment to eliminate hazardous materials and secondary leakage occurs. Built-in wheels eliminate the need for a separate dolly or other transport; Help to provide you with the most effective and low cost safety solutions.

65-Gallon Wheeled Poly-Overpack Salvage Drum

Spill Capacity (Gal/L) : 60/228


1 65-Gallon Wheeled Poly-Overpack Salvage Drum **125** pcs 50cm×40cm absorbent pad, **20** pcs 7.6cm×120cm absorbent sock, **10** pcs 45cm×45cm absorbent pillow, **10** pcs hazamat disposal bags, **10** pcs rope, **1** pair of Rax-9202 safety goggles, **1** pair of safety gloves, **1** pc user manual, weight (Kgs.):**25.5**



Use Guiding of Spill Emergency Treatment Equipments

1. Spill Sources and Risk Judgments

Look for spill source and determine the hazards of the materials: assess the risks of leakage based on chemical labels and MSDS of the spilled materials (including flammable, explosive, reactive and toxic, etc).



2. Personal Protective Equipment (PPE) Arrangements

In spill treatment site, you should wear necessary personal protective equipment (including protective clothing, respirators, gloves, glasses, chemical boots, etc.). If you cannot determine the source of spilled material, you need to consider the possibility of the occurrence of the most serious consequences, to arrange the PPE for the serious consequence, so as to safely deal with spills.



3. Spill Prevention and Control

Control the spill, by closing or restricting valves, or taking appropriate measures. If container spills occur, it is noted that the container should be kept in an upright position.



4. Spill Treatment

Assess the level of spill. After spill area is controlled, use appropriate SYSBEL spill kits in a timely manner. The absorbent pads in the package are for small-scale spill; Socks can absorb spill, overlapping circle is for controlling leakage range, socks and pillows can be used to deal with large-scale leakage. The absorbent materials or hazardous materials after treatment should be properly transferred to the chemical-proof disposal bag or accidental release SYSBEL overpack salvage drum. As required by the local regulations, they will be transferred to the professional waste disposal facility for special treatment.



5. Pollution Elimination

Clean personal protective equipment to prevent secondary pollution.



6. Spill Treatment Report

Prepare the treatment report of spills, and report to upper-level management.

