## **Drench Hose**

Drench hose units, WG7011R & WG7012R are for deck mounting. Ideal for rinsing any part of user's eye, face or body. Under ANSI Z358.1-2014, drench hose units supplement, but do not replace, other types of emergency equipment.

 To meet the standard of Emergency Eyewash and Shower Equipment in ANSI Z358.1-2014 and AS4775-2007;

• Single or double spray head is optional, which has dust cover;

• Forged brass squeeze valve activated by plastic lever handle. Valve has replaceable stainless steel seat for exceptional durability. Valve closes when lever handle is released.

• 1.5m soft PVC tube wrapped by PE film relief from rust and leakage, and internal filter to remove impurities from the water flow.

Spray heads provide even, continued and comfortable fluid to irrigate the eye;
Eye wash exceeds minimum water flow of 0.4GPM(1.5LPM) at 210kPa

(30psi);

• Deck flange for countertop mounting, flange has a position to fix the unit.



OSHA°CE

36

It complies with the regulations in ANSI Z358.1–2014 standard and OSHA 29 CFR 1910.151(C) issued by ANSI has acquired CE Certification



Drench Hose									
Product	Main Material	Color	Flow Speed (L/min)	Inlet & Outlet	Pressure (bar)	Packing size L*W*H/cm	G.W. (kgs.)	Model	
Drench Hose (Single)	304SS	Red	6	G1/2"	3-6	27. 4×19. 6×15. 6	1.4	WG7011R	
Drench Hose (Double)	304SS	Red	10	G1/2"	3-6	27. 4×19. 6×15. 6	1.6	WG7012R	

## Wall Mounted Eye/Face Wash

- Application:Eye/Face wash for wall mounting. The bowl guides waste water to drain and keeps floor clean
- Materials: AES plastic + 304 Stainless Steel
- AES plastic has weather resistance properties and applys to indoors or outdoors
- With good acid-proof,alkali prevention performances,304SS is ideal for harsh environment
- Activated by push handle easily
- The coin slot hidden faucet aerator is easy to remove and clean
- Dust cover is removed once unit started
- Comply with ANSI Z358.1-2014 and AS 4775-2007

## Pedestal Mounted Eye/Face Wash

- Application:Free standing,fixed on the ground when it is not convenient for wall-mounting
- Materials: AES plastic + 304 Stainless Steel
- AES plastic has weather resistance properties and applys to indoors or outdoors
- With good acidproof ,alkali prevention performances,304SS is ideal for harsh environment
- Be activated by push handle or foot pedal easily
- The coin slot hidden faucet aerator is esay to remove and clean
- · Dust cover is removed once unit started
- Comply with ANSI Z358.1-2014 and AS 4775-2007



WG/023

......

6



SYSBEL

WG7033F

WG7033FY

Eye/Face Wash												
Product	Main Material	Water Bowl		Flow				Decking size	0.14	NI 14/		
		Material	Diameter x Height (cm)	Rate (L/min)	Inlet	Outlet	Pressure	Packing size LxWxH(cm)	G.W. (kgs.)	N.W. (kgs.)	Certification	Model
Wall Mounted Eye/ Face Wash	304 Stainless Steel	304 Stainless Steel	32×9.5	11.4	1/2'' -	1-1/4"	210kPa or 2.1bar or 30psi	58×36×25.5	3.1	1.9	ANSI Z358.1	WG7023
		AES plastic	32×9.5			1-1/4"			2.9	1.7	AS 4775	WG7023Y
Pedestal Mounted Eye/Face Wash		304 Stainless Steel	32×9.5			1"		95×35×26.5	5.8	4.0	CSA - CE	WG7033F
		AES plastic	32×9.5			1"			5.6	3.8	UE UE	WG7033FY

