

Model 65 Scoop™ Stretcher

- Uncouples at both ends of the stretcher to gently scoop up the patient, or uncouple only one end to use a scissor-type closing motion
- Supports patient in the position found, reducing risk of further injury
- Narrow control-end frame improves handling in confined areas
- Telescoping tubes provide adjustable length for patients of various heights
- Folds for compact storage
- Can be used with Model 385-C Storage/Carrying Case (0311700)
- Lightweight, easy to carry
- Certifications: CE



Model 561 Scoop™ Wall Bracket.....No. 0819876

Model 65 Scoop™ Mount Bracket.....No. 0832259

	0000452	0000451	0000450	0000449	0000448	0000447	0000325
Restraint	Model 430	Model 430	Model 430	Model 430-P	Model 430-P	Model 430-P	Model 436
Color	Black	Black	Orange	Black	Orange	Black	Black
Buckle	Metal	Metal	Metal	Plastic	Plastic	Plastic	Plastic
Length	1524 mm	2134 mm	2134 mm	1524 mm	2134 mm	2134 mm	2134 mm
# Pieces	2	1	1	2	1	1	2
Speed-Clip	No	No	No	No	No	No	Yes

Model 60 Aluminum Backboards

- Sturdy sheet aluminum is permanently fastened to a tubular aluminum frame, forming a lightweight backboard
- Multiple restraint and handhold openings enable easy handling and various restraint configurations
- Folds in half to store in a variety of ambulance compartments
- Includes three nine-foot nylon patient restraints with quick-release metal buckles
- Available with three full-width runners mounted permanently to the underside of the backboard for convenient handling grip
- Additional restraint openings allow greater flexibility in restraint configurations for using cravats to immobilize the patient
- Certifications: CE



Model 60 with restraints.....No. 0106000

Model 60-2 with runners and restraintsNo. 0106020

Model 60-4 with runners and restraints.....No. 0106040

	LENGTH (MAX)	LENGTH (MIN)	LENGTH (FOLDED)	WIDTH	OPEN DEPTH	FOLDED DEPTH	WEIGHT	LOAD LIMIT
65 IMPERIAL	79 IN	65 IN	47 IN	17 IN	3 IN	4 IN	16 LB	350 LB
65 METRIC	200 CM	165 CM	119 CM	43 CM	8 CM	10 CM	7 KG	159 KG
60 IMPERIAL	71.25 IN	—	36 IN	18 IN	1.5 IN	2.5 IN	17.5 LB	350 LB
60 METRIC	181 CM	—	91 CM	46 CM	4 CM	6 CM	8 KG	159 KG
60-2 IMPERIAL	72.25 IN	—	36 IN	18 IN	2.25 IN	2.5 IN	14 LB	350 LB
60-2 METRIC	184 CM	—	91 CM	46 CM	6 CM	6 CM	6 KG	159 KG
60-4 IMPERIAL	78 IN	—	39 IN	18 IN	2.25 IN	2.5 IN	15 LB	350 LB
60-4 METRIC	198 CM	—	99 CM	46 CM	6 CM	6 CM	7 KG	159 KG