

The Survivor features a low-profile bezel that doesn't interfere with gear and equipment. A reinforced D-ring provides forward-hanging orientation. Safety rated for Class I, Div. 1 environments.



Low-profile design doesn't interfere with gear and equipment



Interchangeable Smoke-Cutter® plugs for preferred beam pattern:

- Black plug significantly reduces peripheral light for a tighter beam
- Amber plug reduces peripheral light and eye fatigue caused by glare



Strong spring-loaded clip securely grabs onto belts and gear; D-ring provides forward hanging orientation

Rubber dome push-button switch easy to use with gloves

Rugged nylon polymer body is virtually indestructible

No tools needed to change batteries

Specialized optic combines low profile with strong performance and a wide beam

DUAL POWER SOURCE:
Rechargeable NiMH battery also accepts 4 "AA" alkaline batteries



High, low, emergency flash and moonlight modes:

- High for a super-bright, smoke piercing beam: 175 lumens; 405m beam distance; runs 3.5 hours (NiMH); runs 4 hours (alkaline)
- Low for longer run time: 60 lumens; 237m beam distance; runs 13 hours (NiMH); runs 15 hours (alkaline)
- Flash for signaling: runs 8 hours
- Moonlight mode provides low-level lighting for battery conservation: runs 20 days

Optimized electronics provide regulated intensity

Unbreakable polycarbonate lens with silicone anti-scratch coating is assembled in a heavy-duty bezel

Class I & II, Division 1, Groups C,D,E,F,G, Class III, T-Code: T4; Class I, Division 2, Groups A,B,C,D, T-Code: T4

Rack meets requirements of NFPA 1901-14.1.10.2 (2016) mounted in any position

IPX4 water-resistant; 2m impact resistance tested

7.6 in. (17.92 cm); NiMH: 18 oz. (510g); Alkaline: 13.17 oz. (373g)

Limited Lifetime Warranty
Visit streamlight.com for full warranty information

See reverse for item numbers

90515	Survivor - 230V AC/12V DC - Yellow
90525	Survivor - 230V AC/12V DC - Black
90505	Survivor - 230V AC/12V DC - Orange
90516	Survivor - 240V AC/12V DC - Yellow
90506	Survivor - 240V AC/12V DC - Orange
90526	Survivor - 240V AC/12V DC - Black
90503	Survivor - 120V/100V AC/12V DC Smart Charge - Orange
90513	Survivor - 120V/100V AC/12V DC Smart Charge - Yellow
90523	Survivor - 120V/100V AC/12V DC Smart Charge - Black
90512	Survivor - 120V/100V AC Fast Charge - Yellow
90502	Survivor - 120V/100V AC Fast Charge - Orange
90522	Survivor - 120V/100V AC Fast Charge - Black
90519	Survivor - 12V DC - Fast Charge - Yellow
90528	Survivor - 12V DC Fast Charge - Black
90509	Survivor - 12V DC Fast Charge - Orange
90510	Survivor - (WITHOUT CHARGER) - Yellow
90500	Survivor - (WITHOUT CHARGER) - Orange
90520	Survivor - (WITHOUT CHARGER) - Black
90541	Survivor - Alkaline Model - Yellow
90540	Survivor - Alkaline Model - Orange
90545	Survivor - Alkaline Model - Black

